



PATENT ABSTRACTS OF JAPAN

(11) Publication number: 04060148 A

(43) Date of publication of application: 26.02.1992

(51) Int. Cl. F02D 43/00

F02D 41/02, F02D 41/04, F02P 5/15

(21) Application number: 02173573

(22) Date of filing: 29.06.1990

(71) Applicant: FUJI HEAVY IND LTD

(72) Inventor: MATSUURA TAKASHI

(54) CONTROL DEVICE OF TWO-CYCLE ENGINE

(57) Abstract:

PURPOSE: To smoothly decrease torque fluctuation so as to improve a feeling at deceleration time by switching combustion to stratified combustion and reduction-controlling a fuel injection amount in this combustion system when fuel is cut at the deceleration time or overspeed preventing time.

CONSTITUTION: During operation of an engine, an engine speed N_e and a fuel injection amount G_f , respectively obtained by an engine speed detecting part 51 and a fuel injection pulse width calculating part 53, are input to a combustion system decision part 56 where stratified combustion in the case of low and intermediate load operation and uniform combustion in the case of high load operation are decided. When a fuel cut or fuel resetting is decided in a fuel/ resetting decision part 61, its decision signal is input with the decision signal of a combustion system to a switching control part 62 so as to switch the combustion system forcedly to the stratified combustion at fuel cut and reset time by a fuel injection timing determining part 54

and an ignition timing determining part 55. Here, a cut coefficient α is gradually decreased at the fuel cut time from a cut/reset coefficient calculating part 63, and a reset coefficient β is gradually increasingly determined at the reset time.

COPYRIGHT: (C)1992,JPO&Japio

